

# Product datasheet

Specifications



## APC Smart-UPS C 3000VA LCD 230V

SMC3000I

### Overview

<b>Presentation</b>	Intelligent and efficient network power protection from entry level to scalable runtime. Ideal UPS for servers, point-of-sale, routers, switches, hubs and other network devices.
<b>Lead time</b>	Usually Ships within 2 Weeks

### Main

<b>Main Input Voltage</b>	230 V
<b>Other Input Voltage</b>	220 V 240 V
<b>Main Output Voltage</b>	230 V
<b>Rated power in W</b>	2100 W
<b>Rated power in VA</b>	3000 VA
<b>Product or component type</b>	Uninterruptible power supply (UPS)
<b>Input Connection Type</b>	IEC 320 C20
<b>output connection type</b>	8 IEC 320 C13 1 IEC 320 C19
<b>Number of rack unit</b>	0U
<b>Battery type</b>	Lead-acid battery
<b>Provided equipment</b>	CD with software Documentation CD USB cable
<b>Range of product</b>	Smart-UPS

### Batteries & Runtime

<b>Run Time</b>	<a href="#">View Runtime Graph</a>
<b>Extended runtime</b>	0
<b>Number of battery filled slots</b>	0
<b>Number of battery free slots</b>	0
<b>Battery recharge time</b>	3 h
<b>Number of battery replacement quantity</b>	1
<b>Battery life</b>	3...5 year(s)
<b>Replacement battery</b>	<a href="#">APCRBC150</a>
<b>Battery charger power</b>	183 W rated

Excluding VAT, FCA Jabal Ali & are subject to change – check with your local distributor.

## General

Number of power module	0
Number of power module filled slots	0
Number of power module free slots	0
product web sub-family	Entry level
Redundant	No

## Physical

Colour	Black
Height	43.5 cm
width	19.7 cm
Depth	54.4 cm
Net weight	43 kg
Mounting location	Front
Mounting preference	No preference
Mounting mode	Not rack-mountable
Two post mountable	0
USB compatible	Yes

## Input

Input voltage limits	170...300 V adjustable 180...287 V
Network frequency	47...63 Hz

## Output

Harmonic distortion	Less than 5 % at full load
Maximum configurable power in VA	3000 VA
Maximum configurable power in W	2100 W
UPS type	Line interactive
Wave type	Sine wave
Output frequency	50 Hz sync to mains

## Conformance

Product certifications	C-Tick CE EAC GOST SABS VDE UK PSTI
Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018

## Environmental

Acoustic level	45 dBA
----------------	--------

Heat dissipation	135 Btu/h
Operating altitude	0...10000 ft
Ambient air temperature for operation	0...40 °C
Ambient air temperature for storage	-15...45 °C
Storage altitude	0.0000000000...15240.0000000000 m
Relative humidity	0...95 %
Storage Relative Humidity	0...95 %

## Communications & Management

control panel	Multifunction LCD status and control console
Free slots	0
Alarm	Alarm when on battery : distinctive low battery alarm : configurable delays

## Surge Protection and Filtering

Surge energy rate	300 J
Noise suppression	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	76.2 cm
Package 1 Width	69.9 cm
Package 1 Length	38.1 cm
Package 1 Weight	51 kg

## Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[How this information helps you >](#)

### Environmental footprint

Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	<b>3920</b>
---	-------------

Environmental Disclosure

[Product Environmental Profile](#)

## Use Better

### Materials and Substances

Packaging made with recycled cardboard	<b>Yes</b>
--	------------

Packaging without single use plastic	<b>No</b>
--------------------------------------	-----------

EU RoHS Directive	<b>Compliant with Exemptions</b>
-------------------	----------------------------------

REACH Regulation	<a href="#">REACH Declaration</a>
------------------	-----------------------------------

### Energy efficiency

Optimized Energy Efficiency	<b>Energy efficient product</b>
-----------------------------	---------------------------------

## Use Again

### Repack and remanufacture

Circularity Profile

[End of Life Information](#)

Removable battery

**User replaceable**

WEEE



The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

---

Take-back

Yes

---

Image of product / Alternate images

Alternative

---

