

Product datasheet

Specifications



APC Easy UPS On-Line, 1000VA/800W, Tower, 230V, 3x IEC C13 outlets, Intelligent Card Slot, LCD, Extended runtime

SRV1KIL

Overview

Presentation	High quality, Double-conversion On-line UPS designed for essential power protection needs even in the most unstable power conditions.
Lead time	Usually in Stock

Main

Main Input Voltage	230 V
Product or component type	Uninterruptible power supply (UPS)
Other Input Voltage	220 V 240 V
Main Output Voltage	230 V
Other Output Voltage	220 V 240 V
Rated power in W	800 W
Rated power in VA	1000 VA
Input Connection Type	IEC 60320 C14
Output connection type	3 IEC 60320 C13
Cable length	1.50 m
Number of cables	1
Provided equipment	1 IEC 60320 C13 to Schuko power cable 1 IEC 60320 C13 to C14 power cable 1 USB cable 1 RS-232 configuration cable 1 battery cable user manual

Batteries & Runtime

Battery type	Lead-acid battery
Battery voltage	36 V
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	4.5 h
Battery life	3...5 year(s)
Battery charger power	175 W rated

General

Number of power module filled slots 0

Number of power module free slots 0

Redundant No

Physical

Colour Black (RAL 7010)

Height 23.8 cm

Width 29 cm

Depth 40 cm

Net weight 24 kg

Mounting location Front

Mounting preference No preference

Mounting mode Not rack-mountable

USB compatible No

Mounting position Vertical

Input

Input voltage limits 110...285 V half load
160...280 V full load

Network frequency 40...70 Hz auto sensing

Output

Maximum configurable power in VA 1000 VA

Maximum configurable power in W 800 W

Output frequency 50/60 Hz +/- 3 Hz sync to mains

Harmonic distortion 3 %

UPS type Double conversion online

Wave type Sine wave

Efficiency 88 % (full load)

Additional information Configurable for 220 : 230 or 240 nominal output voltage

Bypass type Internal bypass (automatic and manual)

Crest factor 3 : 1

Conformance

Product certifications CE
UKCA
EAC
TISI

Standards EN/IEC 62040-1:2019/A11:2021
EN/IEC 62040-2:2006/AC:2006
EN/IEC 62040-2:2018

Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 % non-condensing
Operating altitude	0...3000 m
Ambient air temperature for storage	-20...50 °C
Storage Relative Humidity	0...95 % non-condensing
Storage altitude	0...15000 m
Acoustic level	50 dBA
Heat dissipation	372 Btu/h
IP degree of protection	IP20

Communications & Management

Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm
Free slots	1
Control panel	Multifunction LCD status and control console

Surge Protection and Filtering

Surge energy rate	600 J
-------------------	-------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	2
Package 1 Height	35.5 cm
Package 1 Width	47 cm
Package 1 Length	52.5 cm
Package 1 Weight	26.7 kg

Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
RoHS exemption information	Yes

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

Recommended replacement(s)