

Product datasheet

Specifications



APC Easy UPS, 2200VA, Tower, 230V, 4x CEE 7/3 Schuko outlets, AVR

BVX2200LI-GR

Overview

Lead time Usually in Stock

Main

Main Input Voltage 230 V AC 1 phase

Main Output Voltage 230 V AC 1 phase

Rated power in W 1200 W

Rated power in VA 2200 VA

Input Connection Type Schuko

Output connection type 4 Schuko

Cable length 1.22 m

Number of cables 1

Battery type Lead-acid battery

Provided equipment User manual

Batteries & Runtime

Number of battery filled slots 0

Number of battery free slots 0

Battery recharge time 8 h

Battery voltage 24 V

Battery capacity 9.0 Ah

Battery life 2...3 year(s)

Replacement battery [APCRBC177](#)

Extended runtime 0

General

Max runtime 240 min

Number of power module free slots 0

Number of power module filled slots 0

Redundant No

UPS size	WS
----------	----

Physical

Colour	Black
Height	19 cm
Width	14 cm
Depth	39 cm
Net weight	12.2 kg
Mounting support	Floor
Mounting preference	No preference
Mounting mode	Not rack-mountable
Two post mountable	0
USB compatible	No

Input

Network frequency	50/60 Hz +/- 5 Hz auto-sensing
Input voltage limits	140...300 V 230 V AC
Cos phi	0.54

Output

Maximum configurable power in W	1200 W
Output frequency	50/60 Hz +/- 1 Hz sync to mains
UPS type	Line interactive
Wave type	Stepped approximation to a sinewave
Full load runtime	00:01:00 1200 W
Graph display	1
Half load runtime	00:08:30 600 W
Maximum configurable power in VA	2200 VA
Transfer time	6 ms typical : 10 ms maximum

Conformance

Product certifications	CE CB
Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018
Equipment protection policy	Lifetime : 50000 euros

Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 % non-condensing
Operating altitude	0...3000 m
Ambient air temperature for storage	-15...40 °C
Storage Relative Humidity	0...95 % non-condensing

Storage altitude	0...3000 m
Acoustic level	40 dBA
IP degree of protection	IP20

Surge Protection and Filtering

Surge energy rate	273 J
-------------------	-------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	29.7 cm
Package 1 Width	49.5 cm
Package 1 Length	23.5 cm
Package 1 Weight	13.2 kg
SCC14	10731304404627

Offer Sustainability

REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
RoHS exemption information	Yes

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

Recommended replacement(s)