

# Product datasheet

Specifications



## Easy UPS 3S Parallel Kit

E3SOPT002

### Overview

<b>Presentation</b>	Parallel kit including one cable (5m) for Easy UPS 3S parallel systems. Up to four UPSs can be paralleled for capacity or redundancy.
<b>Lead Time</b>	Usually Ships within 6 Weeks

### Main

<b>Cable Length</b>	500 cm
---------------------	--------

### Physical

<b>Width</b>	22.9 cm
<b>Net Weight</b>	0.45 kg

### Environmental

<b>Ambient Air Temperature For Operation</b>	0...40 °C
<b>Relative Humidity</b>	0...95 % non-condensing
<b>Operating Altitude</b>	0...3281 ft

### Packing Units

<b>Unit Type Of Package 1</b>	PCE
<b>Number Of Units In Package 1</b>	1
<b>Package 1 Height</b>	17.5 cm
<b>Package 1 Width</b>	22 cm
<b>Package 1 Length</b>	40 cm
<b>Package 1 Weight</b>	1.022 kg


Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications


## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

[Learn more >](#)

## Well-being performance

 Mercury Free

 Rohs Exemption Information [Yes](#)

**Reach Regulation** [REACH Declaration](#)

**Eu Rohs Directive** Pro-active compliance (Product out of EU RoHS legal scope)  
[EU RoHS Declaration](#)

**China Rohs Regulation** [China RoHS declaration](#)  
Product out of China RoHS scope. Substance declaration for your information