

Product datasheet

Specifications



APC Easy UPS On-Line, 6kVA/6kW,
Tower, 230V, Hard wire 3-
wire(1P+N+E) outlet, Intelligent
Card Slot, LCD, Extended Runtime

SRV6KIL

Overview

Presentation High quality, Double-conversion On-line UPS designed for essential power protection needs even in the most unstable power conditions.

Lead Time Usually in Stock

Main

Main Input Voltage 230 V

Product Or Component Type Uninterruptible power supply (UPS)

Other Input Voltage 220 V
240 V

Main Output Voltage 230 V

Other Output Voltage 220 V
240 V

Rated Power In W 6000 W

Rated Power In Va 6000 VA

Output Connector Type Hard wire 3-wire (1P + N + E) 1

Provided Equipment 1 USB cable
1 RS-232 configuration cable
1 external battery pack
1 battery cable
1 user manual

Batteries & Runtime

Run Time [View Runtime Graph](#)

Efficiency [View Efficiency Graph](#)

Battery Type Lead-acid battery

Battery Voltage 240 V

Number Of Battery Filled Slots 0

Number Of Battery Free Slots 0

Battery Recharge Time 5 h

Battery Life 3...5 year(s)

Battery Charger Power 1170 W rated

General

Number Of Power Module Filled Slots 0

Number Of Power Module Free Slots	0
Redundant	No

Physical

Colour	Black (RAL 7010)
Height	36.8 cm
Width	38 cm
Depth	48.5 cm
Net Weight	73 kg
Mounting Location	Front
Mounting Preference	No preference
Mounting Mode	Not rack-mountable
Usb Compatible	Yes
Mounting Position	Vertical

Input

Input Voltage Limits	110...300 V 60 % load 176...300 V full load
Number Of Input Connectors	1 hard wire 3-wire (1P + N + E)
Network Frequency	40...70 Hz auto sensing

Output

Maximum Configurable Power In Va	6000 VA
Maximum Configurable Power In W	6000 W
Output Frequency	50/60 Hz +/- 3 Hz sync to mains
Harmonic Distortion	1 %
Ups Type	Double conversion online
Wave Type	Sine wave
Efficiency	94 % (full load)
Additional Information	Configurable for 220 : 230 or 240 nominal output voltage
Bypass Type	Internal bypass (automatic and manual)
Crest Factor	3 : 1

Conformance

Product Certifications	CE UKCA EAC TISI
Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018

Environmental

Ambient Air Temperature For Operation	0...40 °C
Relative Humidity	0...95 % non-condensing

Operating Altitude	0...3000 m
Ambient Air Temperature For Storage	-15...60 °C
Storage Relative Humidity	0...95 % non-condensing
Storage Altitude	0...15000 m
Acoustic Level	55 dBA
Heat Dissipation	1172 Btu/h
Ip Degree Of Protection	IP20

Communications & Management

Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm
Emergency Power Off	Yes
Free Slots	1
Control Panel	Multifunction LCD status and control console

Surge Protection and Filtering

Surge Energy Rate	600 J
-------------------	-------

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	46 cm
Package 1 Width	57 cm
Package 1 Length	58 cm
Package 1 Weight	79 kg

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

[Learn more >](#)

Well-being performance

✓ Toxic Heavy Metal Free

✓ Mercury Free

✓ Rohs Exemption Information [Yes](#)

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Compliant
[EU RoHS Declaration](#)

China Rohs Regulation [China RoHS declaration](#)
Pro-active China RoHS declaration (out of China RoHS legal scope)
