

# Product datasheet

Specifications



## APC Easy UPS 1 Ph Line Interactive, 1000VA, Tower, 230V, 4 Schuko CEE 7 outlets, AVR, LCD

SMV1000I-GR

### Overview

Lead Time	Usually in Stock
-----------	------------------

### Main

Main Input Voltage	230 V
Input Voltage	220 V 240 V
Main Output Voltage	230 V
Rated Power In W	700 W
Rated Power In Va	1000 VA
Input Connection Type	IEC 60320 C14
Output Connection Type	4 Schuko CEE 7
Number Of Cables	1
Battery Type	Lead-acid battery
Provided Equipment	Documentation CD User manual USB cable

### Batteries & Runtime

Run Time	<a href="#">View Runtime Graph</a>
Efficiency	<a href="#">View Efficiency Graph</a>
Number Of Battery Filled Slots	0
Number Of Battery Free Slots	0
Battery Recharge Time	4 h
Battery Voltage	24 V
Battery Charger Power	37 W rated
Battery Life	3...5 year(s)
Replacement Battery	<a href="#">APCRBCV206</a>
Extended Runtime	0

### General

Number Of Power Module Free Slots	0
Number Of Power Module Filled Slots	0
Redundant	No

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Ups Size	WS
----------	----

## Physical

Colour	Black
Height	22 cm
Width	16 cm
Depth	41 cm
Net Weight	13.6 kg
Mounting Preference	No preference
Mounting Mode	Not rack-mountable
Two Post Mountable	0
Usb Compatible	No

## Input

Network Frequency	45...65 Hz auto-sensing
Input Voltage Limits	165...290 V

## Output

Maximum Configurable Power In W	700 W
Output Frequency	50/60 Hz +/- 1 Hz unsynchronised
Crest Factor	3 : 1
Ups Type	Line interactive
Wave Type	Sine wave
Graph Display	1
Maximum Configurable Power In Va	1000 VA
Transfer Time	2-6 ms typical : 12 ms maximum

## Conformance

Product Certifications	CE
Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018

## Environmental

Ambient Air Temperature For Operation	0...40 °C
Relative Humidity	0...95 % non-condensing
Operating Altitude	0...3000 m
Ambient Air Temperature For Storage	-10...40 °C
Storage Relative Humidity	0...95 % non-condensing
Storage Altitude	0...15000 m
Acoustic Level	45 dBA
Ip Degree Of Protection	IP20

## Communications & Management

Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm
-------	--

## Surge Protection and Filtering

Surge Energy Rate	190 J
-------------------	-------

## Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	33.9 cm
Package 1 Width	27.2 cm
Package 1 Length	50.8 cm
Package 1 Weight	16.6 kg

## Contractual warranty



Warranty	2 years repair or replace
----------	---------------------------

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

[Learn more about Green Premium >](#)

## Well-being performance

	Mercury Free	
<hr/>		
	Rohs Exemption Information	<a href="#">Yes</a>
<hr/>		
<hr/>		
Reach Regulation		<a href="#">REACH Declaration</a>
<hr/>		
Eu Rohs Directive		Compliant
		<a href="#">EU RoHS Declaration</a>
<hr/>		
China Rohs Regulation		<a href="#">China RoHS declaration</a>
		Pro-active China RoHS declaration (out of China RoHS legal scope)
<hr/>		
Weee		The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
<hr/>		