

# Product datasheet

Specifications



## APC Easy UPS 1 Ph Line Interactive, 3kVA, Tower, 230V, 4 Schuko CEE 7 outlets, AVR, LCD

SMV3000AI-GR

### Overview

Lead Time Usually in Stock

### Main

Main Input Voltage	230 V
Input Voltage	220 V 240 V
Main Output Voltage	230 V
Rated Power In W	2100 W
Rated Power In Va	3000 VA
Input Connection Type	IEC 60320 C20
Output Connection Type	4 Schuko CEE 7
Number Of Cables	1
Battery Type	Lead-acid battery
Provided Equipment	Documentation CD User manual USB cable

### Batteries & Runtime

Run Time	<a href="#">View Runtime Graph</a>
Efficiency	<a href="#">View Efficiency Graph</a>
Number Of Battery Filled Slots	0
Number Of Battery Free Slots	0
Battery Recharge Time	4 h
Battery Voltage	48 V
Battery Charger Power	99 W rated
Battery Life	3...5 year(s)
Replacement Battery	<a href="#">APCRBCV209</a>
Extended Runtime	0

### General

Number Of Power Module Free Slots	0
Number Of Power Module Filled Slots	0
Redundant	No

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Ups Size	WS
----------	----

## Physical

Colour	Black
Height	24 cm
Width	18 cm
Depth	45.5 cm
Net Weight	25.2 kg
Mounting Preference	No preference
Mounting Mode	Not rack-mountable
Two Post Mountable	0
Usb Compatible	No

## Input

Network Frequency	45...65 Hz +/- 1 Hz auto-sensing
Input Voltage Limits	165...295 V

## Output

Maximum Configurable Power In W	2100 W
Output Frequency	50/60 Hz +/- 1 Hz unsynchronised
Crest Factor	3 : 1
Ups Type	Line interactive
Wave Type	Sine wave
Graph Display	1
Maximum Configurable Power In Va	3000 VA
Transfer Time	2-6 ms typical : 12 ms maximum

## Conformance

Product Certifications	CE
Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018

## Environmental

Ambient Air Temperature For Operation	0...40 °C
Relative Humidity	0...95 % non-condensing
Operating Altitude	0...3000 m
Ambient Air Temperature For Storage	-10...40 °C
Storage Relative Humidity	0...95 % non-condensing
Storage Altitude	0...15000 m
Acoustic Level	45 dBA
Ip Degree Of Protection	IP20

## Communications & Management

Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm
-------	--

## Surge Protection and Filtering

Surge Energy Rate	125 J
-------------------	-------

## Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	41.05 cm
Package 1 Width	31.9 cm
Package 1 Length	60.1 cm
Package 1 Weight	28.9 kg

## Contractual warranty



Warranty	2 years repair or replace
----------	---------------------------

# Sustainability

**Green Premium™** label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

[Learn more about Green Premium >](#)

## Well-being performance

	Mercury Free	
	Rohs Exemption Information	Yes
Reach Regulation	<a href="#">REACH Declaration</a>	
Eu Rohs Directive	Compliant	<a href="#">EU RoHS Declaration</a>
China Rohs Regulation	<a href="#">China RoHS declaration</a> Pro-active China RoHS declaration (out of China RoHS legal scope)	
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins	